

Thapar Technology Campus, Bhadson Road  
Patiala-147004, Punjab India  
Phone: +91 175 2393869, 70

Email: [pushap.raj@thapar.edu](mailto:pushap.raj@thapar.edu); [harjee.banga@thapar.edu](mailto:harjee.banga@thapar.edu)

URL: Thapar.edu

**Enquiry No.** TIET/CS/HB/20-21/20184C

**Date :** January 13, 2021

**Sub:** Request for Quotation(s) for the Supply **Single Phase H-bridge IGBT based inverter stack and Bidirectional DC-DC converter**

Dear Sir

We shall be grateful if you kindly let us have your lowest **quotations** for the following materials. THE QUOTATIONS SHOULD REACH THE UNDERSIGNED **LATEST BY January 25, 2021 @ 11:00 Am** through **courier or e-mail** accompanied by appropriate illustrative literature/catalogues/pamphlets/technical details, samples and specifications as the case may be. **On the quotation envelope/ subject the Enquiry Number & Date should be mentioned on the top of the Envelope/mail subject.**

Sr. No.	Item Name	Qty.
1.	Single Phase H-bridge IGBT based inverter stack and Bidirectional DC-DC converter	As per Annexure I

**The offer sent by you must furnish the following details:**

- |   |  |
|---|--|
| 1. Name, Make & specifications of each item.                    | 6. <b>Delivery FOR Central Stores TIET, Patiala</b>  |
| 2. <b>Price Breakup itemwise with MRP. (Treat it mandatory)</b> | 7. Insurance, Freight & other charges if any.  |
| 3. Educational discount if any.                                 | 8. Minimum Delivery Period.  |
| 4. <b>Validity of quotation should be at least 60 Days.</b>     | 9. <b>Payment terms. Net 30 days against delivery &amp; satisfactory installation at Thapar Institute, Patiala</b> |
| 5. <b>GST %</b>   | 10. Guarantee / Warranty Information.  |
|   | 11. <b>Also please share your Companies Turnover and Market Share along with the offer.</b>                        |

Regards,

**Head Commercial**

## Annexure I

Description of Equipment	Specifications	Nos. of Equipment
<b>Single Phase H-bridge IGBT based inverter stack and Bidirectional DC-DC converter</b> Must operate individually (either buck or boost) and in combination	400V, 15A (inverter)  400V, 10A (DC-DC converter)	2, 1